



TÜRK STANDARDLARI ENSTİTÜSÜ
TÜRK STANDARDLARINA UYGUNLUK BELGESİ
TURKISH STANDARDS INSTITUTION
CERTIFICATE OF CONFORMITY TO TURKISH STANDARDS

Markanın Tanımı Description of the Mark
TSE veya/or  veya/or T S E

BELGE NUMARASI REFERENCE NUMBER OF LICENCE	000134-TSE-08/04
BELGENİN İLK VERİLİŞ TARİHİ DATE OF FIRST ISSUE OF LICENCE	24.04.2012
BELGENİN SON GEÇERLİLİK TARİHİ LICENCE VALID UNTIL	23.03.2024
BELGE SAHİBİ KURULUŞUN ADI NAME OF THE LICENCE HOLDER	İZOCAM TİCARET VE SANAYİ ANONİM ŞİRKETİ
BELGE SAHİBİ KURULUŞUN ADRESİ ADDRESS OF THE LICENCE HOLDER	ALTAYÇEŞME MAH. ÇAMLI SK. NO:21 /4 MALTEPE İSTANBUL/TÜRKİYE
ÜRETİM YERİ ADI NAME OF THE MANUFACTURING PLACE	İZOCAM TİCARET VE SANAYİ ANONİM ŞİRKETİ
ÜRETİM YERİ ADRESİ ADDRESS OF THE MANUFACTURING PLACE	DİLOVASI 41455 GEBZE KOCAELİ / TÜRKİYE
İPTAL EDİLEN BELGE NUMARASI (Varsa) INDICATION OF SUPERSEDED LICENCE (if any)	000134-TSE-08/03
TESCİLLİ TİCARİ MARKASI REGISTERED TRADE MARK	İZOCAM
İLGİLİ TÜRK STANDARDI RELATED TURKISH STANDARD	TS EN 13162+A1 / 02.04.2015
BELGE KAPSAMI SCOPE OF LICENCE	

THERMAL INSULATION PRODUCTS FOR BUILDINGS-FACTORY MADE MINERAL WOOL (MW) PRODUCTS
1) COMMERCIAL MODEL: "TAŞYÜNÜ ARA BÖLME LEVHASI"
REACTION TO FIRE: A1
THERMAL CONDUCTIVITY (λ): 0,035 W/M.K
THICKNESS LEVEL: T4
DIMENSIONAL STABILITY UNDER SPECIFIED TEMPERATURE AND HUMIDITY: DS(70, 90)
SHORT TERM WATER ABSORPTION CLASS: WP
LONG TERM WATER ABSORPTION CLASS BY PARTIAL IMMERSION: WL(P)
COATING: UNCOATED BOARD
PLACE OF USE: THESE PRODUCTS CANNOT BE USED IF COMPRESSIVE CREEP IS NEEDED
2) COMMERCIAL MODEL: "TAŞYÜNÜ DIŞ CEPHE LEVHASI"
REACTION TO FIRE: A1
THERMAL CONDUCTIVITY (λ): 0,035 W/M.K
THICKNESS LEVEL: T4
DIMENSIONAL STABILITY UNDER SPECIFIED TEMPERATURE AND HUMIDITY: DS(70, 90)

e-imzalı/e-signed

10.02.2023

On Behalf Of The Head Of Certification Center
AKDOĞAN BULUT

MANAGER OF THE TSE ISTANBUL CERTIFICATION
DEPT. P.

*This certificate also shows that the production place of the certified product meets the requirements of Institute.

*This certificate under any circumstances cannot be changed, duplicated partially or in a way that makes it difficult to read and erasure cannot be done.

*TSE * Address: Çayırova Tren İstasyonu Yanı ÇAYIROVA/GEBZE * Telephone: 2627231273* Fax: 2627231606

*TSE HEAD OF CERTIFICATION CENTER; Address: Necatibey Cad. No:112 06100 Bakanlıklar/ANKARA – Telephone: 0 312 416 64 81 / 416 64 27, Fax:0 312 416 66 17 E-mail

:bmb@tse.org.tr , web : www.tse.org.tr





TÜRK STANDARDLARI ENSTİTÜSÜ
TÜRK STANDARDLARINA UYGUNLUK BELGESİ
TURKISH STANDARDS INSTITUTION
CERTIFICATE OF CONFORMITY TO TURKISH STANDARDS



BELGE KAPSAMI (000134-TSE-08/04nolu belge devamı) : İZOCAM TİCARET VE SANAYİ ANONİM ŞİRKETİ
İLGİLİ TÜRK STANDARDI(RELATED TURKISH STANDARD) TS EN 13162+A1 / 02.04.2015

SHORT TERM WATER ABSORPTION CLASS: WP
LONG TERM WATER ABSORPTION CLASS BY PARTIAL IMMERSION: WL(P)
COATING: GLASS FIBRE COATED
PLACE OF USE: THESE PRODUCTS CANNOT BE USED IF COMPRESSIVE CREEP IS NEEDED
3) COMMERCIAL MODEL: "TAŞYÜNÜ YÜZER DÖŞEME LEVHASI"
REACTION TO FIRE: A1
THERMAL CONDUCTIVITY (λ): 0,035 W/M.K
THICKNESS LEVEL: T4
DIMENSIONAL STABILITY UNDER SPECIFIED TEMPERATURE AND HUMIDITY: DS(70, 90) SHORT TERM WATER ABSORPTION CLASS: WP
LONG TERM WATER ABSORPTION CLASS BY PARTIAL IMMERSION: WL(P)
COMPRESSIVE STRENGTH: CS(10/Y)5
COATING: UNCOATED BOARD
PLACE OF USE: THESE PRODUCTS CANNOT BE USED IF COMPRESSIVE CREEP IS NEEDED
4) COMMERCIAL MODEL: "TAŞYÜNÜ MANTO R+"
REACTION TO FIRE: A1
THERMAL CONDUCTIVITY (λ): 0,037 W/M.K
THICKNESS LEVEL: T5
DIMENSIONAL STABILITY UNDER SPECIFIED TEMPERATURE AND HUMIDITY: DS(70,90)
SHORT TERM WATER ABSORPTION CLASS: WP
LONG TERM WATER ABSORPTION CLASS BY PARTIAL IMMERSION: WL(P)
COMPRESSIVE STRENGTH: CS(10/Y)20
COATING: UNCOATED BOARD
PLACE OF USE: THESE PRODUCTS CANNOT BE USED IF COMPRESSIVE CREEP IS NEEDED
5) COMMERCIAL MODEL: "TAŞYÜNÜ MANTOLAMA LEVHASI"
REACTION TO FIRE: A1
THERMAL CONDUCTIVITY (λ): 0,039 W/M.K
THICKNESS LEVEL: T5
DIMENSIONAL STABILITY UNDER SPECIFIED TEMPERATURE AND HUMIDITY: DS(70, 90) SHORT TERM WATER ABSORPTION CLASS: WP
LONG TERM WATER ABSORPTION CLASS BY PARTIAL IMMERSION: WL(P)
COMPRESSIVE STRENGTH: CS(10/Y) 30
COATING: UNCOATED BOARD
PLACE OF USE: THESE PRODUCTS CANNOT BE USED IF COMPRESSIVE CREEP IS NEEDED
6) COMMERCIAL MODEL: "TAŞYÜNÜ TERAS ÇATI LEVHASI"
REACTION TO FIRE: A1
THERMAL CONDUCTIVITY (λ): 0,039 W/M.K
THICKNESS LEVEL: T4
DIMENSIONAL STABILITY UNDER SPECIFIED TEMPERATURE AND HUMIDITY: DS(70, 90)
SHORT TERM WATER ABSORPTION CLASS: WP
LONG TERM WATER ABSORPTION CLASS BY PARTIAL IMMERSION: WL(P)
COMPRESSIVE STRENGTH: CS(10/Y) 50
COATING: UNCOATED BOARD
PLACE OF USE: THESE PRODUCTS CANNOT BE USED IF COMPRESSIVE CREEP IS NEEDED

e-imzalı/e-signed

10.02.2023

On Behalf Of The Head Of Certification Center
AKDOĞAN BULUT

MANAGER OF THE TSE ISTANBUL CERTIFICATION
DEPT. P.

*This certificate also shows that the production place of the certified product meets the requirements of Institute.

*This certificate under any circumstances cannot be changed, duplicated partially or in a way that makes it difficult to read and erasure cannot be done.

*TSE * Address: Çayırova Tren İstasyonu Yanı ÇAYIROVA/GEBZE * Telephone: 2627231273* Fax: 2627231606

*TSE HEAD OF CERTIFICATION CENTER; Address: Necatibey Cad. No:112 06100 Bakanlıklar/ANKARA – Telephone: 0 312 416 64 81 / 416 64 27, Fax:0 312 416 66 17 E-mail

:bmb@tse.org.tr , web : www.tse.org.tr

